U.S. Application No.: 10/660,732 Attorney Docket No.: 9988.057.00-US

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- 1. (Currently Amended) A motor-shaft structure for a clothes dryer, the clothes dryer comprising including a drying drum rotatably mounted in a body, a motor bracket fixed to a bottom of an inside of the body, a motor mounted on the motor bracket for generating a rotating power, the motor having a motor shaft and a fan coupled to the motor shaft, the motor shaft comprising a chamfer disposed between the fan and the motor, the chamfer <u>facilitating</u> eonfigured to facilitate removal of the fan from the motor shaft.
- 2. (Previously Presented) The motor shaft structure as claimed in claim 1, wherein the chamfer in the motor shaft has a D-cut form.
- 3. (Previously Presented) The motor shaft structure as claimed in claim 1, wherein the chamfer is disposed between the motor and the motor bracket.
 - 4. (Currently Amended) A laundry dryer comprising:
 - a motor bracket fixed to a bottom of the dryer;
- a motor mounted on the motor bracket, the motor including a motor shaft extending therefrom; and

U.S. Application No.: 10/660,732 Attorney Docket No.: 9988.057.00-US

a fan coupled with the motor shaft, wherein the motor shaft includes a chamfer <u>disposed</u> between the motor and the motor bracket, the chamfer [[for]] cooperating with a tool to prevent the motor shaft from rotating when the fan is removed from the motor shaft.

- 5. (Canceled)
- 6. (Previously Presented) The laundry dryer as claimed in claim 4, wherein the chamfer has a substantially D-cut form.
 - 7. (Canceled)
- 8. (Previously Presented) The laundry dryer as claimed in claim 4, wherein the chamfer is disposed between the motor and the fan.
 - 9. (Currently Amended) A laundry dryer comprising:
 - a motor bracket fixed to a bottom of the dryer;
- a motor mounted on the motor bracket, the motor including a motor shaft extending therefrom; and
- a fan coupled with the motor shaft, wherein the motor shaft includes a chamfer facilitating eonfigured to facilitate removal of the fan from the motor shaft.

10. (Canceled)